



NO Dust! No Cleaning! No Damage! Increased Insulating Value!

This unique window blinds system has been used in prestigious buildings around the world, and is now available to the homeowner. Blinds Between the Glass are sealed in a dust free environment. They require no cleaning while maintaining their new appearance, and are protected from damage, unlike external blinds.

Ideal for windows, doors and office or home partitions.

Lift & Tilt Internal Blinds. For Smaller Windows 14-41 inches Wide

Available in white only.

- The blind is controlled by two magnetic sliders.
- Moving the horizontal outer slide operator to the left or right, will cause the blind slats to rotate between open or closed.
- Moving the vertical outer slide operator down will raise the blind, moving the slider up lowers the blind.

Slimline Lift & Tilt Blinds. For Windows 12-80 inches Wide.

- Slimline blinds are available in white, almond, grey, tan, off-white, silver or gold.
- The blind is controlled by a cord providing the lift and tilt action.



SSLT LIFT & TILT



Insulated between layers of glass allows easy cleaning without damage to the blind.



CUSTOM blinds are now available for door & window applications, bringing contemporary convenience to the home or office.

SLIMLINE SL20A & SL20C



The unique blind design decreases internal heating by limiting amounts of infrared and UV radiation.



External mounted assemblies allow the ease of light and privacy control.

SSLT2 Lift & Tilt Specifications

The SSLT2 Lift & Tilt internal mini-blind requires a minimum overall unit thickness of 1".

The slat is 0.5" x .008" aluminum alloy and is painted with a polyester ultraviolet high resistant finish. For optimum blind operation, slats should be open when raising or lowering the blind. A locking mechanism located on the handle prevents the blind from drifting or sliding when the blind is in the raised position. Available in white.

Due to the mechanisms in this system, it is recommended that the SL20C blind as listed below, be used in units over 14sqft.

- Min/Max width 14 / 45 inches
- Min/Max height 12 / 89 inches
- Operator type Sliders (1 for tilt, 1 for lift)

SL20A Tilt Only Specifications

The SL20A internal mini-blind requires a minimum overall unit thickness of 1".

The slat is 0.5" x .008" aluminum alloy, painted with low emissivity paint with a polyester ultraviolet high resistant finish. Available in grey, white, off-white, almond, silver, tan or gold.

- Min/Max width 12 / 80 inches
- Min/Max height 10 / 106 inches
- Operator types: Knob or Wand.

SL20C Lift & Tilt Specifications

The SL20C model uses an integral cord loop to raise or lower the blind slats. Easy accessibility to the cord loop ensures adjustment of the blinds. Optimum slat positioning can be achieved by making small adjustments when pulling to the right or left on the cord. Minimum overall unit thickness required is 1".

For optimum blind operation, slats should be open when raising or lowering the blind. Available in grey white, off-white, almond, silver, tan or gold.

- Min/Max width 12 / 80 inches
- Min/Max height 10 / 106 inches
- Operator types Cord loop

Overall thickness of units over 14 sqft will exceed 1". Please contact our sales department for further information

Limited Warranty

Internal Blind 3 years

Operators/Components 1 year

Sealed Unit 5 years